

NASA

Technical Memorandum 89875

AVSCOM

Technical Report 87-C-7

Thermo-Oxidatively Stable Condensation Polyimides Containing 1,1,1-Triaryl-2,2,2-Trifluoroethane Dianhydride and Diamine Monomers

William B. Alston

Propulsion Directorate

U.S. Army Aviation Research and Technology Activity—AVSCOM

Lewis Research Center

Cleveland, Ohio

and

Roy F. Gratz

Mary Washington College

Fredericksburg, Virginia

Prepared for the

Symposium on Recent Advances in Polyimides and
Other High Performance Polymers

sponsored by the American Chemical Society

Reno, Nevada, July 13-16, 1987



(NASA-TM-89875) THERMO-OXIDATIVELY STABLE
CONDENSATION POLYIMIDES CONTAINING
1,1,1-TRIARYL-2,2,2-TRIFLUOROETHANE
DIANHYDRIDE AND DIAMINE MONOMERS (NASA) 5

Available: NTIS HC A02/MF A01

CSCL 11B G3/27

N87-22048

Unclas
0072111

THERMO-OXIDATIVELY STABLE CONDENSATION POLYIMIDES CONTAINING
1,1,1-TRIARYL-2,2,2-TRIFLUOROETHANE DIANHYDRIDE
AND DIAMINE MONOMERS

William B. Alston
Propulsion Directorate
U.S. Army Aviation Research and Technology Activity - AVSCOM
Lewis Research Center
Cleveland, Ohio 44135

and

Roy F. Gratz
Department of Chemistry, Geology, and Physics
Mary Washington College
Fredericksburg, Virginia 22401


SUMMARY

The presence of the hexafluoroisopropylidene (6F) connecting group in aryl dianhydrides used to prepare aromatic polyimides provides high glass transition temperature (T_g) polyimides that exhibit excellent thermo-oxidative stability. The purpose of this study was to determine if a trifluorophenylethylidene (1-phenyl-2,2,2-trifluoroethane, 3F) connecting group would have a similar effect as a 6F group on the thermo-oxidative stability of aromatic polyimides. A new dianhydride containing the 3F connecting group was synthesized. This new 3F dianhydride and a previously reported (refs. 1 to 3) aromatic diamine also containing the 3F connecting group were used together and in various combinations with known diamines or known dianhydrides, respectively, to prepare new condensation polyimides which contained the 3F group in one or both of the monomers comprising the polymer repeat unit. Known polyimides, including some with the 6F connecting linkage, were also prepared for comparison purposes. The new 3F containing polymers and the analogous comparison 6F polymers were prepared by condensation polymerization via the traditional amic-acid polymerization method in N,N-dimethylacetamide (DMAc) solvent. The amic-acid solutions, with two exceptions, had inherent viscosities greater than 0.45 dl/g, indicating that high molecular weight polymers had been formed. Structure-to-property relationships correlating inherent viscosity to the basicity of those diamine monomers which contained 3F and 6F connecting linkages were observed and explained in a prior report (ref. 3). The solutions were cast as amic-acid films and then thermally converted into polyimide films at 300 to 500 °C, usually 350 °C, in a nitrogen atmosphere. The polyimide films were then pulverized into molding powders which, in turn, were processed into neat resin discs at temperatures and pressures as high as 468 °C/34.5 MPa. Additional resin discs were processed with similar conditions from molding powders of some 3F monomer combinations that were prepared using other techniques as described in reference 3. These techniques included precipitation of the amic-acid molding powders from DMAc amic-acid solutions, thermal or chemical imidization of the dried precipitated amic-acid powders, and preparation from stoichiometric amounts of diamine and diacid-diester monomer mixtures. The T_g's of these films and resin discs were then determined by thermomechanical analysis (TMA)


and were the subject of a prior report (ref. 3) which identified two new polyimides of $T_g \geq 371^\circ\text{C}$ (3F dianhydride/paraphenylene diamine (PPDA), $T_g \sim 370^\circ\text{C}$, and pyromellitic dianhydride (PMDA)/3F diamine, $T_g \sim 440^\circ\text{C}$). The thermal and thermo-oxidative stability of these 3F polyimide films and the comparison 6F polyimide films were then determined by thermogravimetric analysis (TGA). The isothermal weight losses of the films and the resin discs at 316°C , 371°C , and also at 371°C under 0.5 MPa (~ 5 atm) air pressure were then determined (using a weight loss/unit surface area basis). The results of these studies identified two new 3F containing polyimides (3F dianhydride/PPDA and 6F dianhydride/3F diamine) with low rates of weight loss/unit surface area compared to the known very oxidatively stable 6F dianhydride/PPDA and PMDA/6F diamine resins. The study also showed that the resin discs exhibited the same overall trends in weight loss/unit surface area as their respective films, however, the weight loss per unit surface area of the discs was about an order of magnitude greater. This was presumably due to some mechanical degradation induced during the grinding of the molding powders and/or a greater internal (thus, unmeasured) surface area in the resin discs compared to the films. These overall results indicate that polyimides containing the 3F linkage exhibit thermal and thermo-oxidative stability comparable to polyimides containing the 6F linkage. These thermo-oxidative stability results, combined with the prior T_g results (ref. 3), show that further development of the 3F connecting linkage in aryl dianhydride and aryl diamine monomers to produce high T_g , thermo-oxidatively stable polyimides suitable for 371°C resin and composite applications continues to be warranted.

REFERENCES


1. Kray, W.D. and Rosser, R.W., J. Org. Chem., 1977, 42, 1186-1189.
2. Alston, W.B., in "High Temperature Polymer Matrix Composites" NASA CP-2385, 1985, pp. 187-205. (Also, U.S. Army AVSCOM-TR-85-C-7).
3. Alston, W.B. and Gratz, R.F., in "Recent Advances in Polyimide Science and Technology," Society of Plastics Engineers: Poughkeepsie, NY, 1987, pp. 1-15. (Also NASA TM-87113, and U.S. Army AVSCOM-TR-85-C-18).




6F DIANHYDRIDE, 6FDA



3F DIANHYDRIDE, 3FDA



6F DIAMINE, 6FDAM



3F DIAMINE, 3FDAM

1. Report No. NASA TM-89875 AVSCOM-TR-87-C-7		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle Thermo-Oxidatively Stable Condensation Polyimides Containing 1,1,1-Triaryl-2,2,2-Trifluoroethane Dianhydride and Diamine Monomers				5. Report Date	
				6. Performing Organization Code 505-63-01	
7. Author(s) William B. Alston and Roy F. Gratz				8. Performing Organization Report No. E-3551	
				10. Work Unit No.	
9. Performing Organization Name and Address NASA Lewis Research Center and Propulsion Directorate, U.S. Army Aviation Research and Technology Activity - AVSCOM, Cleveland, Ohio 44135				11. Contract or Grant No.	
				13. Type of Report and Period Covered Technical Memorandum	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546 and U.S. Army Aviation Systems Command, St. Louis, Mo. 63120				14. Sponsoring Agency Code	
15. Supplementary Notes Prepared for the Symposium on Recent Advances in Polyimides and Other High Performance Polymers, sponsored by the American Chemical Society, Reno, Nevada, July 13-16, 1987. William B. Alston, Propulsion Directorate, U.S. Army Aviation Research and Technology Activity - AVSCOM, Lewis Research Center; Roy F. Gratz, Dept. of Chemistry, Geology and Physics, Mary Washington College, Fredericksburg, Virginia 22401.					
16. Abstract Nine new condensation polyimides containing the trifluorophenylethylidene linkage were synthesized by the amic-acid route. Several other polyimides, including some with the hexafluoroisopropylidene linkage, were also prepared as controls. Amic-acid solutions were characterized by determining their inherent viscosities prior to thermal conversion into polyimide films. Glass transition temperatures (T_g), thermogravimetric analysis (TGA), and isothermal weight loss data (at 316 °C, 371 °C, and 371 °C under 0.5 MPa air pressure) were obtained for the films. The films were pulverized into molding powders which, in turn, were thermally processed under pressure into neat resin discs. The discs were also characterized by T_gs and 316 and 371 °C isothermal weight losses. The film study identified two new polyimides with T_gs greater than 371 °C and two new polyimides with low rates of weight loss. The resin discs exhibited the same overall trends in T_g and weight loss as the respective films, however the weight loss per unit surface area was always greater, presumably due to voids or to mechanical degradation induced during preparation of the molding powders. The overall results indicate that polyimides containing the trifluorophenylethylidene linkage have T_gs and thermo-oxidative stability comparable to polyimides con- taining the hexafluoroisopropylidene group.					
17. Key Words (Suggested by Author(s)) Polyimides; Condensation polymers; High temperature stability; Glass transition temperature (T_g); Thermally and thermo- oxidatively stable			18. Distribution Statement Unclassified - unlimited STAR Category 27		
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of pages 5	
				22. Price* A02	